

BLCVI7202812IRW

1.0 Megapixel 720P Water-Proof IR HDCVI Camera - Varifocal



Features

- 1/3" 1.0 Megapixel Cmos
- 25/30/50/60fps@720p
- High Speed, long distance real-time transmission
- Day/Night (ICR), AWB, AGC, BLC, 3D-DNR
- Varifocal 2.8-12mm, lens 3MPX
- Max. IR LEDs length 35mt., 36 Led
- IP66, DC12V

HDCVI

BLCVI7202812IRW**Specifications**

Model	
BLCV7202812IRW	
Camera	
Image Sensor	1/3" 1.0 Megapixel CMOS
Effective Pixels	1280(H)x720(V)
Electronic Shutter	4/25s~1/45,000s
Video Frame Rate	1280×720@25 fps; 1280×720@30 fps; 1280×720@50 fps; 1280×720@60 fps
Synchronization	Internal
Min Illumination	0.01Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC HDCVI high definition video output/ CVBS
Camera Features	
Max. IR LEDs Lenght	35m, Smart IR, 36 LED
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	2D/3D
OSD Menu	NO
Lens	
Focal Lenght	2.8-12mm Varifocal, Lend 3MPX
Mount Type	M12

BLCVI72036IRW

General	
Power Supply	DC12V±10%
Power Consumption	Max 4.9W
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions (WxDxH)	Φ73mm x197mm
Weight	490g
Others	Default: bracket included

Note: Photo is an example

Securitem Ltd.

Via Sant'Agostino,13

20181 Cesano Maderno (MB)

Tel: +39-0362-1855440

Email: info@setik.biz

www.setik.biz

*Design and specifications are subject to change without prior notification.

© 2014 Securitem Ltd.