











TRIBRID DVR SERIE AHD 720P CLOUD P2P - SETIK

Model

ST5A43H 4ch DVR/NVR, support 4@720 (25Fps) / 4@960H (12Fps), 1 HD, RJ-45 LAN, 1 HDMI, 1 VGA, 2 USB, 1 IN / OUT Audio

 $\tt ST5A83H$ 8ch DVR/NVR, support 8@D1 (25Fps) / 8@960H (12Fps) , 1 HD, RJ-45 LAN, 1 HDMI, 1 VGA, 2 USB, 1 IN / OUT Audio

Features

- > Third-Generation video compression of H264 (Main Profile)
- > This DVR supports six different operations at the same time: recording, playback, network transmission, backup, mobile control and interface operation
- > Powerful CMS features for multiple DVR, which can display 64 large-scale centralized management of the video
- > Audio In/Out > Video Output
- > Remote visibility with the app VmeyeCloud
- > Support all Browser Client (IE, Chrome, Mozilla, Safari) remote parameter settings, preview, download video data network supports PPPoE, DHCP & Static IP address & DDNS

Air Browser Supported









- > Cloud Function p2p for Remote access without Public IP
- > Dedicated high-reliability file system monitoring, which greatly enhance the protection of video data security
- > Over 30 Languages supported (Italiano, English, France, Spain, ecc.)
- > All Mobile Phone Supported

symbian







::: BlackBerry.



Specifications

Model	ST5A43H	ST5A83H
System		
Main Processor	High performance embedded microprocessor	
Operating System	Embedded LINUX	
System Resources	multi-channel real-time recording and playback, multi-channel net operation for several persons, USB backup	
Operation Interface	16-bit true-color graphical menu interface and mouse support	
Video		
Input	4 channel BNC	8 channel BNC
Standard	PAL(625Line, 50hertz)	
Audio		
Input	1 channel,BNC, 1.0Vp-p,75Ω	
Output	1 channel ,RCA, 200-3000mV,5KΩ	
Display		
Interface	1 VGA, HDMI	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4	1/4/8
OSD	Camera title, time, video loss, camera lock, motion detection, recording	
Recording		
Video/Audio Compression	H.264 / G.711	
	4@720P (AHD-M)	8@720P (AHD-M)
Resolution Recording	4@960H (AHD-L)	8@960H (AHD-L)
	2@720P (AHD-M) + 2@720P IP	2@720P (AHD-M) + 2@720P IP
	8@1080P IP	8@1080P IP
Extra Stream	4@CIF	8@CIF
	Analog CVBS	Analog CVBS
Standard Supported	IP Onvif	IP Onvif
отапаата Сарроптоа	AHD (AHD-L / AHD-M)	AHD (AHD-L / AHD-M)
Recording Quality	CBR, VBR(1~6 level, level 6 is the	best)
Recording Mode	Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection, Camera blank, Video loss), Alarm), Stop	
Bit Rate	48-2560Kb/s	
Recording Priority	Manual >Alarm >MD >Regular	
Recording Interval	1~120 min (default: 60 min), Pre-Record: 1~30, Post-Record 10~300	



Video Detection				
Trigger Events	Recording, PTZ movement, Tour, Email, FTP, Buzzer & Screen tips			
Motion Detection	Zones: 396(22×18) detection zones, many levels of Sensitivity setting			
Video Loss & Camera Blank	Support			
Playback & Backup				
Playback Channel	1/4	1/4/8		
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search			
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom			
Backup Mode	Flash drive/ USB HDD/ USB/ Built-in SATA burner/ Network download			
Network				
Ethernet	RJ-45 port (10/100M)			
Network Function	HTTP, TCP/IP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, Alarm Server			
Max Remote Users	10 Users simultaneously			
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information			
Hard Disk				
Hard Disk	1 SATA ports, Up to 4TB.			
HDD Management	HDD hibernation technology, HDD faulty alarm			

Auxiliary Interface		
USB Interface	2 ports, For mouse control & backup	
Environmental		
Power Supply	12V/2A - Power Supply AC 100~240 V, 50/60 Hz	
Power Consumption	< 10W(without HDD)	
Working Environment	-0 ~+55°C / 10~90%RH / 86~106kpa	
Dimension	Smart 1U, 200mm×210mm×45mm	
Weight	1.0KG(without HDD)	



System Connection



Note: Photo is an example

Securitatem Ltd.

Via Sant'Agostino,13 20181 Cesano Maderno (MB)

Tel: +39-0362-1855440 Email: info@setik.biz

www.setik.biz

 $\ensuremath{^*\text{Design}}$ and specifications are subject to change without prior notification.

© 2014 Securitatem Ltd.