

BLIP10-36IRLT (Lite Version)

IP Camera 1.0Mpx, Dual Core DSP, 3.6mm Fixed Lens – Lite Version



Lite

Features

- Image Sensor CMOS 1/4" Silicon Optronics JX-H42 + HI3518E
- Day/Night, ICR, 3DWDR, 3DNR, AGC, OSD
- 3.6mm Fixed
- Illuminator with 12x SMD Leds
- IP66, DC12V
- Onvif Compliant 2.3
- Dahua Motion Detect Compatible starting from Onvif 2.3 Version
- Cloud P2P



qr-code CLOUD



BLIP10-36IRLT (Lite Version)

Specifications

Model		BLIP10-36IRLT
Camera		
Image Sensor	CMOS 1/4" Silicon Optronics JX-H42 + HI3518E	
Effective Pixel	1280(H)x800(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/50~1/10000	
Min Illumination	0.1Lux @ (F1.2, AGC ON), 0 LUX con IR	
S/N Ratio	More than 48db	
Camera Features		
IR LEDs	12x SMD leds	
Day/Night	Auto(ICR) / Color / B/W	
Video Output	N/A	
Backlight Compensation	BLC/HLC/DWDR	
White Balance	Auto / Manual	
Gain Control	Auto / Manual	
Noise Reduction	2D	
Privacy masking	none	
Lens		
Focal Length	3.6mm	
Max Aperture	F1.2	
Focus Control	Manual	
Angle of View	H: 70.5°/44.9°	
Lens Type	Fixed Lens	
Mount Type	M12 Type	
Video		
Compression	H264	
Resolution	720P(1280X720)/D1(704X576)	
Frame Rate	Main Stream	720P@25fps
	Sub Stream	D1@25fps
Bit Rate	H264:1024Kbps~4096Kbps	
Audio		
Compression	none	
Interface	none	
Network		
Ethernet	RJ-45 (10/100Base-T)	
WI-FI	none	
Protocol	IPV4,HTTP,TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, RTP, RTSP	

Compatibility	Onvif 2.3
Max User Access	10 users
Smart Phone	P2P Cloud , Iphone, Ipad, Android, Windows Mobile, Symbian, Blackberry
Network	1 x RJ45, 10/100M, support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
General	
Ingress Protection	IP66
Language Supported	Over 25 Languages (Italian, Francais, English, Poland, Deutscher, etc.)
Onvif	2.3 Support
Mobile Monitor	Support iPhone,Windows Mobile,BlackBerry,Symbian,Android
Working Temperature	-40°~55°
Humidity	<95% RH
Power supply	DC 12V power input (not included)
Power Consumption	4.5W
Size	150mm*70mm

Securitem Ltd.

Via Sant'Agostino,13

20181 Cesano Maderno (MB)

Tel: +39-0362-1855440

Email: info@setik.biz - www.setik.biz

Note: Photo is an example

*Design and specifications are subject to change without prior notification.