

NOTE:

1. Electrical test:

- (1).100% open short & miss wire test;
- (2).Insulation resistance:DC 500V 500MΩ;
- (3).Contactor resistance: 3 ohm Max;


2.RoHS & REACH Compliant.

3.PRINT WORD: As per customers' s requirement

PIN OUT:

CN1				CN2			
WH/OR	1			1	WH/OR		
OR	2			2	OR		
WH/GR	3			3	WH/GR		
GR	6			6	GR		
WH/BL	5			5	WH/BL		
BL	4			4	BL		
WH/BR	7			7	WH/BR		
BR	8			8	BR		

PACKING:



MATERIAL LIST:

④	MINI TIE	PVC/GREY L=**mm	1						
③	OUTER MOLD	PVC 75A/GREY	2		DRAWING		PART NAME	CAT.6 UTP 8P8C TO 8P8C	
②	CONN	RJ45 8P8C PIN GOLD-PLATED TRANSPARENT	2		CUSTOMER			ICON	TOLERANCE
①	CAT. 5E CABLE	UTP CAT. 6 24AWG (7/0.19±0.005) BC*4P+CROSS PVC JACKET/GREY OD:6.0±0.2mm	1		CUSTOMER'S ITEM				X. ±1.00 X.X ±0.50
					APPRO BY	CHECK BY	DRAWN BY	SCALE	MM
NO.	PARTS. NAME	SPECIFICATION STANDARD	QT' Y	REMARK	Jianhong He	Any. zhang	East LI	PAGE	1/1