# **HIKVISION**

# DS-PD2-T10P-WEH Wireless Outdoor Dual-Tech Detector

DS-PD2-T10P-WEH is an external detector that combines advanced technologies such as Tri-technology detection and the Two-way wireless protocol.



## AVAILABLE MODEL

|                         | <b>F</b>   |
|-------------------------|--|
| DS-PD2-D10P-WEH         | Wireless Outdoor Dual-Tech Detector                                  |
| DS-PDB-EX-Wall bracket  | Wall bracket (Need to order separately )                             |
| DS-PDB-EX-Adapter       | Detector Bracket for Extending coverage angle to 90 degrees (Need to |
|                         | order separately, using together with DS-PDB-EX-Wall bracket)        |
| DS-PDB-EX-Fixed bracket | Add two detectors back to back to create 20m perimeter protection    |
|                         | (Need to order separately)   |

\*All bracket need to order separately.

#### MAIN FEATURES

- Microwave + 2 independent PIR
- Two-way Wireless Technology
- 10m Volumetric Coverage
- Alarm: Tamper Alarm, Intruder Alarm
- Built-in walk test buzzer
- Heavy Duty Ultraviolet Filter
- Automatic Temperature Compensation
- Weatherproof Sealed Optics

### SPECIFICATION

| Wireless Outdoor Dual-Tech Detector |                             |  |
|-------------------------------------|-----------------------------|--|
| Detection Range                     | 10m Volumetric coverage 90° |  |
| Detection Speed                     | 0.25m/s ~ 3m/s              |  |
| Animal Immunity                     | 10 kg                       |  |
| Power Supply                        | Built-in 3V Lithium battery |  |
| Transmission frequency              | 433/868 MHz                 |  |
| <b>Operation Temperature</b>        | -30°C ~ +70°C               |  |
| Dimension(L*W*H)                    | 180mm*80mm*105mm            |  |
| Weight                              | 500g (without bracket)      |  |
| Installation Environment            | Outdoor                     |  |