DAHUA-4493

DH-HAC-B3A21P-Z-2712

4-in-1 Lite 2MP outdoor camera

- Dahua Lite 4 in 1 camera
- 2MP@25/30ips
- Switchable 4 in 1 output
- ICR, 0.04 lux, Smart IR 40m
- 2.7~12mm motorized optics
- Digital WDR
- IP67 protection, 3AXIS

Reference / Model	DAHUA-4493 / DH-HAC-B3A21P-Z-2712
2 megapixel 1/2.7 CMOS sensor	
Digital resolution: 1080P (1920x1080), 720P (1280x720), 960H (960x756)	
Frames per second: 25/30 fps @1080P (CVI/TVI/AHD)	
4-in-1 switchable output	
Day/Night mode with removable mechanical filter (ICR)	
0.04 lux F1.7 (color) / 0 lux IR On	
Smart IR: 2 IR LEDs, 40 meters	
2.7 ~ 12 mm motorized optics	
Viewing angle: 33°~102°(H), 19°~53°(V), 38°~125°(D)	
Imaging modes: BLC, HLC, digital WDR, 2D-NR, Mirror, digital Defog.	
Auto and manual white balance	
Auto and manual gain control	
8-zone privacy mask	
Power supply: 12V DC (±30%)	
Power consumption: 6.6W (max.)	

DAHUA-4493

DH-HAC-B3A21P-Z-2712

4-in-1 Lite 2MP outdoor camera

Reference / Model	DAHUA-4493 / DH-HAC-B3A21P-Z-2712
Storage temperature -30°C ~ +60°C (-30°C ~ +60°C)	
Operating temperature -30°C ~ +60°C (-30°C ~ +60°C)	
Relative humidity: <95% (non-condensing)	
IP67 degree of protection	
Metal and plastic housing	
Dimensions: 90.4 (W) x 90.7 (H) x 243.5 mm (W x H) x 243.5 mm (2.5 x 2.5 in)	
Net weight: 390 g	
Gross weight: 530 g	
3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)	