DAHUA-5072

DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP

HDCVI 5MP bullet camera Smart Dual Light Dahua Lite Series

- Dahua Lite Series HDCVI Bullet Camera
- 5MP@25ips
- ICR, 0.01 lux, Smart Dual Light with IR 80 m and white light 60 m
- Motorized lens 2.7-13.5 mm with Smart Zoom Lighting
- 3D NR, DWDR
- Built-in microphone with coaxial audio
- Switchable CVI/TVI/AHD/CVBS output
- IP67 protection
- Power supply 12 V DC

Reference / Model	DAHUA-5072 / DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP
Technical Features	
Dahua Lite Series HDCVI Bullet Camera	
5 MP CMOS sensor	
Maximum resolution of 2880 × 1620	
Minimum illumination 0.01 lux@F1.6 (color), 0.001 lux@F1.6 (B/W), 0 lux (illuminator on)	
80 m IR illumination distance	
60 m white light illumination distance	
Smart Dual Light and Smart Zoom Lighting	
Motorized lens varifocal 2.7~13.5 mm	
Viewing angle: H 32.7°~111.8°, V 18.4°~58.3°, D 37.5°~135.2°	
Video	
CVI/TVI/AHD/CVBS output selectable via DIP Switch	
Supported resolution: 5M (2880 × 1620), 4M (2560 × 1440), 1080P (1920 × 1080), 960H (960 × 576/960 × 480), TVI 5M 16:9 (2960 × 1665)	

DAHUA-5072

DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP

HDCVI 5MP bullet camera Smart Dual Light Dahua Lite Series

Reference / Model	DAHUA-5072 / DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP
Frames per second:	
CVI: 5M@25 ips; 5M@12.5 ips; 4M@25 ips; 1080P@25 ips (PAL).	
AHD: 4M@25 fps (PAL)	
TVI: 5M 16:9@20 ips (PAL)	
CVBS: 960H	
Day/Night Auto (ICR)/Color/B/W mode	
BLC, HLC and DWDR	
3D NR Noise Reduction	
Privacy masking (8 areas)	
Features	
Super Adapt with automatic parameter adjustment	
Audio	
Built-in microphone	
CVI/TVI coaxial audio	
Pickup distance up to 8 m	
Communication interface	
BNC video output (CVI/TVI/AHD/CVBS selectable by DIP Switch)	
Power supply	
12 V DC (±30 %)	
Maximum power consumption 7.4 W (IR on)	
Environmental	
Operating temperature: -30 °C ~ +60 °C	
Relative humidity: < 95 % (non-condensing)	
IP67 protection	
Physical characteristics	
Metal housing	
Wall, ceiling or vertical pole installation	

DAHUA-5072

DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP

HDCVI 5MP bullet camera Smart Dual Light Dahua Lite Series

Reference / Model	DAHUA-5072 / DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP
Dimensions: 209.9 × 90.4 × 90.4 mm (209.9 × 90.4 × 90.4 mm)	
Net weight: 0.54 kg	
Gross weight: 0.70 kg	
3AXIS: Pan 0°~360°, Tilt 0°~90°, Rotation 0°~360°	
Contents	
5 MP HDCVI Bullet Camera **DAHUA-5072** (DH-HAC-HFW1500RP-Z-IL-A-27135-S3-DIP)	
Certifications and standards	
CE-LVD: EN 62368-1	
CE-EMC: EN 55032; EN 55035	