

# TC-NR5005M7-S1

## H.265 5-Channel Videorecorder

Tiandy


Reference: TC-NR5005M7-S1  
Reference Old: TC-NR2005M7-S1  
H.265 5CH 1HDD NVR



### Features

- Third-party Network Cameras Supported
- Up to 4K Resolution Recording
- HDD Quota and Group Management
- Dual Gigabit Network Interfaces
- Support 5-ch Intelligent Analysis Process
- Smart Search&Recording, Plug&Play
- Support ANR Function
- Support N+1 Hot Standby Function
- 1x HDMI, 1x VGA, Same Video Source, Max Resolution 4K
- 1 SATA(Up to 6TB), Alarm I/O 0/1, 2xUSB
- CE, FCC

### Dimensions



DATASHEET	
<b>Specification</b>	
<b>Video/Audio Input</b>	
IP Video Input	5ch
Audio Input	N/A
<b>Network</b>	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	40Mbps
Remote Connection	16 Users, Up to 48ch Videos
Browser	IE8,IE9,IE10,IE11,Chrome30,Firefox24
Mobile Software	P2P&DDNS for IOS&Android (Tiandy: TD Viewer, Neutral: Smartwatchman)
Internet Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPoE/DDNS/NFS/FTP/NTP/H TTPS/RTSP/SMTP/HTTPS/SADP
Email	Activated by Alarm
ANR	Y, Auto download video from camera SD card, Which was stored when disconnection (Only Support Tiandy ANR IP Camera)
Advanced	Remaining Bandwidth Display
<b>Video/Audio Output</b>	
HDMI Output	1-ch Resolution: 3840x2160,2560x1600, 1920x1080,1280x720, 800x600,1024x768,1366x768,1440x900,1280x800
VGA Output	1-ch Resolution: 1920x1080,1280x720,800x600,1024x768,1366x768,1440x900,1280x800 Adjustable Output mode, Self-adaptive Resolution
Frame Rate	Mainstream 25fps(P)/30fps(N) Substream 25fps(P)/30fps(N)
I-Frame Record	Y
Recording Resolution	4K(3840*2160,3264*2448,3296*2472)/6MP(2752*2208,3008*2008,2408*2008) 8)/5MP(2560*1920,2592*1944,2592*1920,2528*2128)/4MP(2560*1440,2592*1520)/3MP(2048*1536)/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output	N/A
Synchronous Playback	1-ch 4K/6MP/5MP/4MP/2-ch 3MP/4-ch 1080P/720P/4CIF Synchronous Playback
<b>Decoding</b>	
Live View/Playback	4K(3840*2160,3264*2448,3296*2472)/6MP(2752*2208,3008*2008,2408*2008) 8)/5MP(2560*1920,2592*1944,2592*1920,2528*2128)/4MP(2560*1440,2592*1520)/3MP(2048*1536)/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Display Split	1/4/6
E-Zoom	Y
<b>Hard Disk</b>	
SATA	1 SATA for 1HDD
E-SATA	N/A
Capacity	Up to 6TB
NTFS Files System	Y
HDD Management	Group and Quota, Customized Recording Days
<b>External Interface</b>	
Network Interface	1X RJ-45 10/100Mbps Self-adaptive Ethernet Interfaces
Serial Interface	N/A
USB Interface	1x USB3.0, 1x USB2.0
Alarm In/Out	0/1
<b>Advance</b>	
NAS	NFS Protocol, Support Manual Backup Only
Plug and Play	Y, Only for Tiandy Cameras
Image Flip	Y, Only for Tiandy Cameras
Hot Standby	N+1
Corridor Mode	Y, 16:9 to 9:16, Only for Tiandy Cameras
Video Analytics(VCA)	Support 5ch Camera VCA Function, including Tripwire/Perimeter/Facial Detection/People Counting/Missing&Foreign Object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection
Smart Search	Quickly Search Target Videos according to Channel No., Records Type, Records Time, File Type and VCA( Only for Tiandy Cameras )
Trigger Recording	Manual/Timing/Motion Detection/Port Alarm/ VCA Alarm/Video Occlusion
Smart Recording	Set Recording Bite Rate for Different Time
Alarm Recording	Pre Alarm Default 10s (5/10/15/60s Optional), Post Alarm Default 10s (10/15/30/60/600s Optional).
One Key Control	Intercom, Recording
Records Format	SDV, Export MP4 in H.264 Format
Records Encryption	Y
Records Tag	Y
Onvif	Onvif(Profile S)
<b>General</b>	
Langue	English, Spanish, Korean, Italian,Turkish,French, Thai, Russian, Traditional Chinese,Polish (Hebrew Optional)
Power Supply	DC12V 2A
Consumption(without HDD)	≤ 10W
Working Temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)
Working Humidity	10 % ~ 90 %
Chassis	1U
Dimensions	42mmx255mmx231mm
Weight	0.8KG (without HDD), 1.4KG (with Packing Box)

